

Masterlift 2.35 Pv

Electro-hydraulic twin-ram lift, 3.5 t, superstructure with flat lifting supports



Application

- ☐ Check-in
- ☐ Wash
- ☐ Repairs and maintenance
- ☐ Testing

Approvals / recommendations

- ☐ Renault
- ☐ ML 2.35 Pv 140-200: Opel
- ☐ ML 2.35 Pv 160-220 xy: Mercedes-Benz, Volkswagen Group
- ☐ ML 2.35 Pv 170-240: BMW / Mini
- ☐ ML 2.35 Pv 160-220 Premium: Volvo

Description:

Steel cassette:

- ☐ Waterproof steel cassette

Hydraulic unit:

- ☐ Hard-chrome plated cylinder
- ☐ Flexible synchronization and safety system
- ☐ Corrosion-free guiding elements
- ☐ Pump unit with immersed motor
- ☐ Hydraulic oil
- ☐ Pneumatic emergency lowering
- ☐ Programmable pushbutton control unit

Superstructure:

- ☐ Stable lifting supports, lengthwise adjustable
- ☐ Rubber-coated, non-skid pads
- ☐ Low minimum height

Standard colours:

- ☐ Pv Standard: zinc coated
- ☐ Pv Premium: zinc coated and painted RAL 9006 – white aluminum

Versions:

Steel cassette:

- ☐ Zinc-coated
- ☐ Coated
- ☐ Self-carrying

Superstructure:

- ☐ Lifting supports in different lengths (120-180, 140-200, 160-220 & 170-240)

Installation:

- ☐ Superstructure on floor
- ☐ Superstructure in floor
- ☐ Ceiling installation

Optional extras:

- ☐ XY-pads
- ☐ Sets of rubber blocks, 40, 60, 80 and 100 mm
- ☐ Traverse

Zinc coating and special colours on request!



Scan the QR-Code
for detailed product information.

Further Information on
www.autopstenhoj.com

AUTOPSTENHOJ GmbH

Sandkampstraße 90
D-48432 Rheine

+49 5971 8602-02

info@autopstenhoj.com

AUTOPSTENHOJ GmbH

Barrit Langgade 188-190
DK-7150 Barrit

+45 76 82 13 30

info@autopstenhoj.com

Technical data

Lifting capacity	3,500 kg
Lifting height	1,950 mm
Working height	2,015 mm + rubber pads
Cylinder diameter	2 x 123 mm
Distance between cylinders	1,335 mm
Lifting / lowering time (high pressure)	approx. 30 sec.
Foundation depth	2,625 mm
Pump unit	3 kW
Hydraulic oil	10 l
Voltage	230 / 400 V – 50 Hz – 16 A

Pv superstructure

Total width min. – max.	120 – 180: approx. 1,200 – 1,800 mm 140 – 200: approx. 1,400 – 2,000 mm 160 – 220: approx. 1,600 – 2,200 mm 170 – 240: approx. 1,700 – 2,400 mm
Min. height	65 mm

